CLAIMS AMENDMENTS

- (currently amended) A thermal indicator for visually determining and 1. monitoring temperature of cooking food, comprising:
 - a body having an orifice; a)
- indicating means capable of moving through the orifice relative to the body b) from a first position to a second position for indicating when a preselected temperature has been reached and that the food is cooked to a desired temperature and doneness; and
- a thermopolymeric switching medium contained within the body for c) allowing said indicating means to dynamically indicate when said preselected temperature has been reached, wherein said thermopolymeric switching medium comprises at least one thermopolymeric material that, when at a temperature below the predetermined temperature, maintains said indicating means at the first position, and that, when at a temperature equal to or higher than the predetermined temperature, yields to permit release of said indicating means to the second position visually indicating that the food is cooked to a desired temperature and doneness.
- (original) The thermal indicator as claimed in Claim 1, wherein the 2. thermopolymeric switching medium is an organic polymer.
- (currently amended) The thermal indicator as claimed in Claim 1, further 3. comprising at least one inert additive selected from the group consisting of sugars, salts, starches, cellulose non-melting metal filings, powdered plastics, polymers, silicensilicone, silicates, chromatography resins, ceramic resins, chalk, glass, sand, air, oils, water, and high boiling liquid polymeric materials, and combinations thereof.
- (original) The thermal indicator as claimed in Claim 3, wherein the inert 4. additive is present in an amount between 0.1% to 99% by weight of thermopolymeric switching medium.

- 5. (original) The thermal indicator as claimed in Claim 3, wherein the inert additive is present in an amount between 5% to 95% by weight of thermopolymeric switching medium.
- 6. (original) The thermal indicator as claimed in Claim 3, wherein the inert additive is present in an amount between 10% to 90% by weight of thermopolymeric switching medium.
- 7. (original) The thermal indicator as claimed in Claim 3, wherein the inert additive is present in an amount between 20% to 80% by weight of thermopolymeric switching medium.
- 8. (original) The thermal indicator as claimed in Claim 1, further comprising at least one interactive additive selected from the group consisting of bee's wax, root extracts, long chain hydrocarbon analogs from the jojoba plant, petroleum distillation analogs, and synthetic organic analogs, and combinations thereof.
- 9. (currently amended) The thermal Indicator as claimed in Claim 8, wherein the at least one interactive additive is selected from the group consisting of short and long chain alcohols, esters, acrylic esters, fluorinated hydrocarbons, docosanol (C22), tricosanol (C23), tetracosanol (C24), pentacosanol (C25), hexacosanol hexacosanol (C26), heptacosanol (C27), octacosanol (C28), nonacosanol (C29), triacontanol (C30) and extended analogs, and combinations thereof.
- 10. (original) The thermal indicator as claimed in Claim 8, wherein the at least one interactive additive is present in an amount between 0.1% to 99% by weight of thermopolymeric switching medium.
- 11. (original) The thermal indicator as claimed in Claim 8, wherein the at least one interactive additive is present in an amount between 5% to 95% by weight of thermopolymeric switching medium.

- (original) The thermal Indicator as claimed in Claim 8, wherein the at least 13. one interactive additive is present in an amount between 20% to 80% by weight of thermopolymeric switching medium.
- (original) The thermal Indicator as claimed in Claim 1, further comprising 14. at least one emulsifier selected from the group consisting of lipids, long chain alcohols, lecithins, glycol lipids, quaternized amines with lipid talls, and charged ionic detergents, and combinations thereof.
- (original) The thermal indicator as claimed in Claim 14, wherein the at 15. least one emulsifier is present in an amount between 0.001% to 10% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 14, wherein the at 16. least one emulsifier is present in an amount between 0.01% to 5% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 14, wherein the at 17. least one emulsifier is present in an amount between 0.1% to 1% by weight of thermopolymeric switching medium.

- 18. (currently amended) A thermal indicator for visually determining and monitoring temperature of cooking food, comprising:
- a) a barrel having an orifice communicating with a cavity within said barrel, said barrel being adapted for insertion into the article to be monitored;
- b) an indicator disposed in said cavity and adapted for sliding travel therein between a retracted position with said indicator partially protruding from said cavity within said barrel indicating the food is in an uncooked state and an extended position indicating that the food is in a cooked state and that the food is cooked to a desired temperature and doneness;
- means for resiliently biasing said indicator away from said retracted
 position and toward said extended position; and
- d) thermopolymeric switching medium for releasably retaining said indicator in said retracted position,

wherein said thermopolymeric switching medium, when at a temperature below the predetermined temperature, maintains said indicator in said retracted position, and when at a temperature equal to or higher than the predetermined temperature, yields to permit release of said indicator, said biasing means urging said plunger into said extended position for visual indication that the food is cooked to a desired temperature and doneness.

- 19. (original) The thermal indicator as claimed in Claim 18, wherein the thermopolymeric switching medium is an organic polymer.
- 20. (currently amended) The thermal indicator as claimed in Claim 18, further comprising at least one inert additive selected from the group consisting of sugars, salts, starches, cellulose non-melting metal filings, powdered plastics, polymers, eilicensilicone, silicates, chromatography resins, ceramic resins, chalk, glass, sand, air, oils, water, and high boiling liquid polymeric materials, and combinations thereof.

- (original) The thermal indicator as claimed in Claim 20, wherein the inert 21. additive is present in an amount between 0.1% to 99% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 20, wherein the inert 22. additive is present in an amount between 5% to 95% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 20, wherein the inert 23. additive is present in an amount between 10% to 90% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 20, wherein the inert 24. additive is present in an amount between 20% to 80% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 18, further comprising 25. at least one interactive additive selected from the group consisting of bee's wax, root extracts, long chain hydrocarbon analogs from the jojoba plant, petroleum distillation analogs, and synthetic organic analogs, and combinations thereof.
- (currently amended) The thermal indicator as claimed in Claim 25, 26. wherein the at least one interactive additive is selected from the group consisting of short and long chain alcohols, esters, acrylic esters, fluorinated hydrocarbons, docosanol (C22), tricosanol (C23), tetracosanol (C24), pentacosanol (C25), hexacosnaol hexacosanol (C26), heptacosanol (C27), octacosanol (C28), nonacosanol (C29), triacontanol (C30) and extended analogs, and combinations thereof.
- (original) The thermal indicator as claimed in Claim 25, wherein the at 27. least one interactive additive is present in an amount between 0.1% to 99% by weight of thermopolymeric switching medium.

- (original) The thermal indicator as claimed in Claim 25, wherein the at 28. least one interactive additive is present in an amount between 5% to 95% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 25, wherein the at 29. least one interactive additive is present in an amount between 10% to 90% by weight of thermopolymeric switching medium.
- (original) The thermal Indicator as claimed in Claim 25, wherein the at 30. least one interactive additive is present in an amount between 20% to 80% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 18, further comprising 31. at least one emulsifier selected from the group consisting of lipids, long chain alcohols, lecithins, glycol lipids, quaternized amines with lipid tails, and charged ionic detergents, and combinations thereof.
- (original) The thermal indicator as claimed in Claim 31, wherein the at 32. least one emulsifier is present in an amount between 0.001% to 10% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 31, wherein the at 33. least one emulsifier is present in an amount between 0.01% to 5% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 31, wherein the at 34. least one emulsifier is present in an amount between 0.1% to 1% by weight of thermopolymeric switching medium.

- (currently amended) A thermal indicator for visually determining and 35. monitoring the temperature of cooking food products, comprising:
- a barrel having an orifice communicating with a cavity within said barrel, a) said barrel being adapted for insertion into the article to be monitored;
- an indicator disposed in said cavity and adapted for sliding travel therein b) between a retracted position indicating the food is in an uncooked state and an extended position indicating the food is in a cooked state and visually indicating that the food is cooked to a desired temperature and doneness;
- means for resiliently biasing said indicator away from said retracted position and toward said extended position; and
- organic thermopolymeric switching medium for releasably retaining said indicator in said retracted position; and
- at least one inert additive selected from the group consisting of sugars. salts, starches, cellulose non-melting metal filings, powdered plastics, polymers, silicone, silicates, chromatography resins, ceramic resins, chalk, glass, sand, air, oils, water, and high boiling liquid polymeric materials, and combinations thereof,

wherein said thermopolymeric switching medium, when at a temperature below the predetermined temperature, maintains said indicator in said retracted position, and when at a temperature equal to or higher than the predetermined temperature, yields to permit release of said indicator, said biasing means urging said plunger into said extended position for visual indication that the food is cooked to a desired temperature and doneness.

- 36. (cancelled).
- (currently amended) The thermal indicator as claimed in Claim 4835, 37. further comprising at least one interactive additive selected from the group consisting of bee's wax, root extracts, long chain hydrocarbon analogs from the jojoba plant, petroleum distillation analogs, and synthetic organic analogs, and combinations thereof.

- (original) The thermal indicator as claimed in Claim 37, further comprising 38. at least one emulsifier selected from the group consisting of lipids, long chain alcohols, lecithins, glycol lipids, quaternized amines with lipid tails, and charged ionic detergents, and combinations thereof.
- (original) The thermal indicator as claimed in Claim 38, wherein the inert 39. additive is present in an amount between 0.1% to 99% by weight of thermopolymeric switching medium, the at least one interactive additive is present in an amount between 0.1% to 99% by weight of thermopolymeric switching medium, and the at least one emulsifier is present in an amount between 0.001% to 10% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 39, wherein the inert 40. additive is present in an amount between 5% to 95% by weight of thermopolymeric switching medium, the at least one interactive additive is present in an amount between 5% to 95% by weight of thermopolymeric switching medium, and the at least one emulsifier is present in an amount between 0.01% to 5% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 40, wherein the inert 41. additive is present in an amount between 10% to 90% by weight of thermopolymeric switching medium, the at least one interactive additive is present in an amount between 10% to 90% by weight of thermopolymeric switching medium, and the at least one emulsifier is present in an amount between 0.1% to 1% by weight of thermopolymeric switching medium.
- (original) The thermal indicator as claimed in Claim 41, wherein the inert 42. additive is present in an amount between 20% to 80% by weight of thermopolymeric switching medium and the at least one interactive additive is present in an amount between 20% to 80% by weight of thermopolymeric switching medium.

(currently amended) The thermal indicator as claimed in Claim 39, 43. wherein the at least one interactive additive is selected from the group consisting of short and long chain alcohols, esters, acrylic esters, fluorinated hydrocarbons, docosanol (C22), tricosanol (C23), tetracosanol (C24), pentacosanol (C25), hexacosnaol hexacosanol (C26), heptacosanol (C27), octacosanol (C28), nonacosanol (C29), triacontanol (C30) and extended analogs, and combinations thereof.